Applicants: Suemasu et al.

Serial No.: 10/820,272

Filing Date: April 8, 2004

Docket No.: 105-63 DIV/RCE II

Page 2

Response to Office Action dated August 25, 2009

IN THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1-8. (Cancelled).

9. (Currently Amended) A metal filling method comprising steps of:

forming a non-through hole which extends from a first surface toward an opposite

surface of a substrate;

forming an oxide layer on an inner peripheral surface portion of the non-through

hole adjacent to the first surface of the substrate, and on a portion of the first surface of the

substrate adjacent to the non-through hole, such that only the oxide layer is layered on the

substrate;

forming a metal layer on the inner peripheral surface portion of the non-through

hole adjacent to the first surface of the substrate, and on the portion of the first surface of the

substrate adjacent to the non-through hole, such that the metal layer is directly adhered to the

oxide layer;

filling the non-through hole with molten metal by relatively reducing pressure in

the non-through hole compared with pressure outside the non-through hole, and allowing the

molten metal to solidify; and

Applicants: Suemasu et al.

Serial No.: 10/820,272

Filing Date: April 8, 2004

Docket No.: 105-63 DIV/RCE II

Response to Office Action dated August 25, 2009

Page 3

removing part of the substrate such that the solidified metal is exposed through

the opposite surface of the substrate.

10. (Previously Presented) The metal filling method according to claim 9, wherein

the non-through hole is filled by immersing the work piece in a molten metal.

11. (Previously Presented) The metal filling method according to claim 10, wherein

the filled metal is solidified by discharging the substrate from the molten metal.

12. (Canceled)

(Previously Presented) The metal filling according to claim 9, wherein part of the 13.

substrate is removed by polishing.

14. (Previously Presented) The metal filling method according to claim 9, wherein

the solidified metal comprises an external section which protrudes from the first surface of the

substrate.

15. (Previously Presented) The metal filling method according to claim 14, wherein

the external section comprises a bump.

16. (Currently Amended) A metal filling method comprising steps of:

forming a through hole which extends through a substrate from a first surface

toward an opposite surface thereof;

forming an oxide layer on an inner peripheral surface portion of the through hole

adjacent to the first surface of the substrate, and on a portion of the first surface of the substrate

adjacent to the through hole, such that only the oxide layer is layered on the substrate;

Applicants: Suemasu et al.

Serial No.: 10/820,272

Filing Date: April 8, 2004

Docket No.: 105-63 DIV/RCE II

Response to Office Action dated August 25, 2009

Page 4

forming a metal layer on the inner peripheral surface portion of the through hole

adjacent to the first surface of the substrate, and on the a portion of the first surface of the

substrate adjacent to the through hole, such that the metal layer is directly adhered to the oxide

layer;

closing an opening of the through hole in the opposite surface of the substrate;

filling the through hole with molten metal by relatively reducing pressure in the

through hole compared with pressure outside the through hole, and allowing the molten metal to

solidify; and

opening the closed opening of the through hole such that the solidified metal is

exposed through the opening of the through hole.

17. (Previously Presented) The metal filling method according to claim 16, wherein

the through hole is filled by immersing the substrate in a molten metal.

18. (Previously Presented) The metal filling method according to claim 17, wherein

the filled metal is solidified by discharging the substrate from the molten metal.

19. (Canceled)

20. (Previously Presented) The metal filling method according to claim 16, wherein

the opening of the through hole is closed using a sealing material.

21. (Previously Presented) The metal filling method according to claim 16, wherein

the solidified metal comprises an external section which protrudes from the first surface of the

substrate.

Applicants: Suemasu et al. Serial No.: 10/820,272 Filing Date: April 8, 2004 Docket No.: 105-63 DIV/RCE II

Response to Office Action dated August 25, 2009

Page 5

22. (Previously Presented) The metal filling method according to claim 21, wherein the external section comprises a bump.